

MODEL SEG-11 - Supply Performance Data

1" X 1/4" Rectangular Slots with 5/16" Frets

Nominal Size		Nom Duct Area, ft2	Core Vel, fpm	100	150	200	250	300	350	400
W	H			Ps	0.01	0.02	0.03	0.04	0.06	0.08
Width	Height									
6"	6"	0.25	CFM	12	18	23	29	35	41	47
			NC	<20	<20	<20	<20	<20	<20	<20
			CFM	26	39	52	65	78	91	104
8"	8"	0.44	NC	<20	<20	<20	<20	<20	<20	23
			CFM	46	69	91	114	137	160	183
			NC	<20	<20	<20	<20	<20	22	27
10"	10"	0.69	CFM	71	107	142	178	213	249	284
			NC	<20	<20	<20	<20	<20	24	29
			CFM	102	153	204	255	306	357	408
12"	12"	1.00	NC	<20	<20	<20	<20	<20	21	27
			CFM	180	271	361	451	541	632	722
			NC	<20	<20	<20	<20	24	30	35
14"	14"	1.36	CFM	228	342	456	570	684	798	912
			NC	<20	<20	<20	<20	26	32	36
			CFM	340	510	680	850	1020	1189	1359
18"	18"	2.25	NC	<20	<20	<20	<20	22	28	34
			CFM	340	510	680	850	1020	1189	1359
			NC	<20	<20	<20	<20	22	28	34
20"	20"	2.78	CFM	340	510	680	850	1020	1189	1359
			NC	<20	<20	<20	<20	22	28	34
			CFM	340	510	680	850	1020	1189	1359
24"	24"	4.00	NC	<20	<20	<20	<20	22	28	34
			CFM	340	510	680	850	1020	1189	1359
			NC	<20	<20	<20	<20	22	28	34

Data determined in accordance with ANSI/ASHRAE Standard 70-1991

Data based on Actual Neck Size = Nominal Neck Size - 1/4"

Ps - Static Pressure, inches w.g.

NC - Noise Criteria based on room attenuation of 10 dB



KEES INCORPORATED
400 S. Industrial Dr.
Elkhart Lake, WI 53020

Phone: (920) 876-3391
Fax: (920) 876-3065
Website: www.kees.com

MODEL SEG-11 - Return Performance Data

1" X 1/4" Rectangular Slots with 5/16" Frets

Nominal Size		Nom Duct Area, ft2	Core Vel, fpm Ps	100	150	200	250	300	350	400
W Width	H Height									
6"	6"	0.25	CFM	12	18	23	29	35	41	47
			NC	<20	<20	<20	<20	<20	<20	<20
8"	8"	0.44	CFM	26	39	52	65	78	91	104
			NC	<20	<20	<20	<20	<20	<20	20
10"	10"	0.69	CFM	46	69	91	114	137	160	183
			NC	<20	<20	<20	<20	<20	<20	24
12"	12"	1.00	CFM	71	107	142	178	213	249	284
			NC	<20	<20	<20	<20	<20	21	26
14"	14"	1.36	CFM	102	153	204	255	306	357	408
			NC	<20	<20	<20	<20	<20	23	29
18"	18"	2.25	CFM	180	271	361	451	541	632	722
			NC	<20	<20	<20	<20	<20	26	32
20"	20"	2.78	CFM	228	342	456	570	684	798	912
			NC	<20	<20	<20	<20	21	28	34
24"	24"	4.00	CFM	340	510	680	850	1020	1189	1359
			NC	<20	<20	<20	<20	24	30	36

Data determined in accordance with ANSI/ASHRAE Standard 70-1991

Data based on Actual Neck Size = Nominal Neck Size - 1/4"

Ps - Static Pressure, inches w.g.

NC - Noise Criteria based on room attenuation of 10 dB



KEES INCORPORATED
400 S. Industrial Dr.
Elkhart Lake, WI 53020

Phone: (920) 876-3391
Fax: (920) 876-3065
Website: www.kees.com